

ALGORITHMS USED BY ELECTRONIC LOGBOOKS FOR THE COMPUTATION OF DEW POINT TEMPERATURE

Name of e-logbook	SEAS
Agency	NOAA National Data Buoy Center (NDBC)
Country	USA
Contact point (name, e-mail)	John Wasserman <John.Wasserman@noaa.gov>
Web site for the software	http://www.aoml.noaa.gov/phod/goos/seas/amverseas_software.php
Version number of e-logbook	8.0 (9.0 version is currently available for beta testing by U.S. VOS personnel, Date of version 9.0 March 2011)
Date of version of e-logbook	September 2008
Version number of algorithm	-(All versions of SEAS use the same algorithm)
Date of version of algorithm	Jan 1977
Name of algorithm	DEWPPT

Variables used as input for the computation of Dew Point Temperature		
Name	Units	Precision required
wet-bulb temperature	deg C	0.1
dry-bulb temperature	deg C	0.1

Variables returned by the algorithm		
Name	Units	Resulted precision
Dew point temperature	deg C	0.1

Pseudocode of the algorithm¹	
<pre> float dewpt(float DryBulb, float WetBulb) { // Paul R. Lowe, "An Approximating Polynomial for the Computation of // Saturation Vapor Pressure", Journal of Applied Meterology, Vol 16, No 1 // January 1977, pp 100-103. // Will return a (float) dew point when passed a drybulb and a wetbulb temperature in Degrees C. // Returns 999 if the dew point can not be computed // dew point based on casio program code // coefficients for saturation vapor pressure // with respect to ice, with respect to water double coef[7][2] = {6.109177956, 6.107799961, 5.03469897E-1, 4.436518521E-1, 1.886013408E-2, 1.428945805E-2, 4.176223716E-4, 2.650648471E-4, 5.824720280E-6, 3.031240396E-6, 4.838803174E-8, 2.034080948E-8, 1.838826904E-10, 6.136820929E-11}; </pre>	

¹ : Possibly based on C++ alike syntax whenever possible; otherwise using original source language that was used

```

double p,q,w,dif,deweql;
int i;
int ice;

if(WetBulb <= 0)
    ice = true;
else
    ice = false;

w=WetBulb;
dif=DryBulb - WetBulb;
if (dif < 0.0)
{
    return 999.0;
}
i=1;
if(ice)i=0;
p=coef[0][i]+w*(coef[1][i]+w*(coef[2][i]+w*(coef[3][i]+w*(coef[4][i]+
w*(coef[5][i]+w*coef[6][i])))));

// use standard atmosphere of 29.92 inches of mercury

p=p-(1013.20789*dif*(0.00066*(1.+w* 0.00115)));
if(p >= 0.0)
{
    q=log(p);
    deweq= (243.5*q-440.8)/(19.48-q);
    return (float) deweq;
}
else
    return 999.0;
}

```

This is the algorithm that is implemented:

```

BOOL CMetDataLoggerDoc::CalculateDewPoint(const double dDryBulb,
                                         const double dWetBulb,
                                         double dDewPoint)                                // in, Celcius degrees
{                                                       // in, Celcius degrees
    BOOL bResult = FALSE;
    double dDifference;
    dDifference = dDryBulb - dWetBulb;

    if (dDifference < 0.0)
        // 999 if the dew point can not be computed
        dDewPoint = 999.;

    else{
        // dew point based on casio program code coefficients for saturation vapor pressure
        // with respect to ice, with respect to water
        //           ice          water
        double coef[7][2] = { 6.109177956,      6.107799961,
                             5.03469897E-1,   4.436518521E-1,
                             1.886013408E-2, 1.428945805E-2,
                             4.176223716E-4, 2.650648471E-4,
                             5.824720280E-6, 3.031240396E-6,
                             4.839903174E-8, 2.034080948E-8,
                             1.838826904E-10, 6.136820929E-11};

        int i;
        if(dWetBulb <= 0)
            i = 0;
        else
            i = 1;

        double p;
        p = coef[0][i] +
            dWetBulb*(coef[1][i] + dWetBulb*(coef[2][i] +
            dWetBulb*(coef[3][i] + dWetBulb*(coef[4][i] +
            dWetBulb*(coef[5][i] + dWetBulb*coef[6][i])))));

        // use standard atmosphere of 29.92 inches of mercury
        p = p - (1013.20789 * dDifference * (0.00066 * (1. + dWetBulb * 0.00115)));
        if(p >= 0.0){
            double q = log(p);
            dDewPoint = (243.5 * q - 440.8) / (19.49 - q);
            bResult = TRUE;
        }
        else
            dDewPoint = 999.;

    }

    return bResult;
}

```