

DRAFT
(NOVEMBER 9, 2000)

LAYOUT FOR THE INTERNATIONAL MARITIME METEOROLOGICAL TAPE (IMMT)
[VERSION IMMT-2]

<i>Element Number</i>	<i>Character Number</i>	<i>Code</i>	<i>Element</i>	<i>Coding procedure</i>
1	1	i _T	Format/temperature indicator	3=IMMT format with temperatures in tenths of °C 4=IMMT format with temperatures in halves of °C 5=IMMT format with temperatures in whole °C
2	2-5	AAAA	Year UTC	Four digits
3	6-7	MM	Month UTC	01 - 12 January to December
4	8-9	YY	Day UTC	01 - 31
5	10-11	GG	Time of observation	Nearest whole hour UTC, WMO specifications
6	12	Q _c	Quadrant of the globe	WMO code table 3333
7	13-15	L _a L _a L _a	Latitude	Tenths of degrees, WMO specifications
8	16-19	L _o L _o L _o L _o	Longitude	Tenths of degrees
9	20		Cloud height (h) and visibility (VV) measuring indicator	0 - h and VV estimated 1 - h measured, VV estimated 2 - h and VV measured 3 - h estimated, VV measured
10	21	h	Height of clouds	WMO code table 1600
11	22-23	VV	Visibility	WMO code table 4377
12	24	N	Cloud amount	Oktas, WMO code table 2700; show 9 where applicable
13	25-26	DD	True wind direction	Tens of degrees, WMO code table 0877; show 00 or 99 where applicable
14	27	i _w	Indicator for wind speed	WMO code table 1855
15	28-29	ff	Wind speed	Tens and units of knots or meters per second, hundreds omitted; values in excess of 99 knots are to be indicated in units of meters per second and I _w encoded accordingly; the method of estimation or measurement and the units used (knots or meters per second) are indicated in element 14
16	30	s _n	Sign of temperature	WMO code table 3845
17	31-33	TTT	Air temperature	Tenths of degrees Celsius
18	34	s _t	Sign of dew-point temperature	0 - positive or zero measured dew-point temperature 1 - negative measured dew-point temperature 2 - iced measured dew-point temperature 5 - positive or zero computed dew-point temperature 6 - negative computed dew-point temperature 7 - iced computed dew-point temperature
19	35-37	T _d T _d T _d	Dew-point temperature	Tenths of degrees Celsius
20	38-41	PPPP	Air pressure	Tenths of hectopascals

Annex IV, p. 2

<i>Element Number</i>	<i>Character Number</i>	<i>Code</i>	<i>Element</i>	<i>Coding procedure</i>
21	42-43	ww	Present weather	WMO code table 4677
22	44	W ₁	Past weather	WMO code table 4561
23	45	W ₂	Past weather	WMO code table 4561
24	46	N _h	Amount of lowest clouds	As reported for C _L or, if no C _L cloud is present, for C _M , in oktas; WMO code table 2700
25	47	C _L	Genus of C _L clouds	WMO code table 0513
26	48	C _M	Genus of C _M clouds	WMO code table 0515
27	49	C _H	Genus of C _H clouds	WMO code table 0509
28	50	s _n	Sign of sea-surface temperature	WMO code table 3845
29	51-53	T _w T _w T _w	Sea surface temperature	Tenth of degrees Celsius
30	54		Indicator for sea-surface temperature measurement	0 - Bucket thermometer 1 - Condenser inlet 2 - Trailing thermistor 3 - Hull contact sensor 4 - "Through hull" sensor 5 - Radiation thermometer 6 - Bait tanks thermometer 7 - Others
31	55		Indicator for wave measurement	Shipborne wave recorder Buoy Other measurement system 0 - Wind sea and swell estimated 1 - Wind sea and swell measured 2 - Mixed wave measured, swell estimated 3 - Other combinations measured and estimated 4 - Wind sea and swell measured 5 - Mixed wave measured, swell estimated 6 - Other combinations measured and estimated 7 - Wind sea and swell measured 8 - Mixed wave measured, swell estimated 9 - Other combinations measured and estimated
32	56-57	P _w P _w	Period of wind waves or of measured waves	Whole seconds; show 99 where applicable in accordance with Note (3) under specification of P _w P _w in the Manual on Codes
33	58-59	H _w H _w	Height of wind waves or of measured waves	Half-meter values. Examples: Calm or less than 1/4m to be encoded 00; 3 1/2m to be encoded 07; 7m to be encoded 14; 11 1/2m to be encoded 23
34	60-61	d _{w1} d _{w1}	Direction of predominant swell waves	Tens of degrees, WMO code table 0877; encoded 00 or 99 where applicable. Blanks = No observation of waves attempted
35	62-63	P _{w1} P _{w1}	Period of predominant swell waves	Whole seconds; encoded 99 where applicable (see under element 32)
36	64-65	H _{w1} H _{w1}	Height of predominant swell waves	Half-meter values (see under element 33)
37	66	I _s	Ice accretion on ships	WMO code table 1751
38	67-68	E _s E _s	Thickness of ice accretion	In centimeters
39	69	R _s	Rate of ice accretion	WMO code table 3551
40	70		Source of observation	0 - Unknown 1 - Logbook 2 - Telecommunication channels 3 - Publications 4 - Logbook 5 - Telecommunication channels 6 - Publications National International data exchange

<i>Element Number</i>	<i>Character Number</i>	<i>Code</i>	<i>Element</i>	<i>Coding procedure</i>
41	71		Observation platform	0 - unknown 1 - Selected ship 2 - Supplementary ship 3 - Auxiliary ship 4 - Automated station/data buoy 5 - Fixed sea station 6 - Coastal station 7 - Aircraft 8 - Satellite 9 - Others
42	72-78		Ship identifier	Ship's call sign or other identifier encoded as follows: 7 characters call sign Columns 72-78 6 characters call sign Columns 72-77 5 characters call sign Columns 72-76 4 characters call sign Columns 72-75 3 characters call sign Columns 72-74
43	79-80		Country which has recruited the ship	According to the two-character alphabetical codes assigned by the International Organization for Standardization (ISO)
44	81		National use	
45	82		Quality control indicator	0 - No quality control (QC) 1 - Manual QC only 2 - Automated QC only (no time-sequence checks) 3 - Automated QC only (inc. time sequence checks) 4 - Manual and automated QC (superficial; no automated time-sequence checks) 5 - Manual and automated QC (superficial; including time-sequence checks) 6 - Manual and automated QC (intensive, including automated time-sequence checks) 7 & 8 - Not used 9 - National system of QC (information to be furnished to WMO)
46	83	i_x	Weather data indicator	1 - Manual 4 - Automatic If present and past weather data included Code tables 4677 and 4561 used 7 - Automatic If present and past weather data included Code tables 4680 and 4531 used
47	84	i_R	Indicator for inclusion or omission of precipitation data	WMO code table 1819
48	85-87	RRR	Amount of precipitation which has fallen during the period preceding the time of observation, as indicated by t_R	WMO code table 3590
49	88	t_R	Duration of period of reference for amount of precipitation, ending at the time of the report	WMO code table 4019
50	89	s_w	Sign of wet-bulb temperature	0 - positive or zero measured wet-bulb temperature 1 - negative measured wet-bulb temperature 2 - iced measured wet-bulb temperature 5 - positive or zero computed wet-bulb temperature 6 - negative computed wet-bulb temperature 7 - iced computed wet-bulb temperature
51	90-92	$T_b T_b T_b$	Wet-bulb temperature	In tenths of degree Celsius, sign given by element 50
52	93	a	Characteristic of pressure tendency during the three hours preceding the time of observation	WMO code table 0200

Annex IV, p. 4

<i>Element Number</i>	<i>Character Number</i>	<i>Code</i>	<i>Element</i>	<i>Coding procedure</i>
53	94-96	ppp	Amount of pressure tendency at station level during the three hours preceding the time of observation	In tenths of hectopascal
54	97	D _S	True direction of resultant displacement of the ship during three hours preceding the time of observation	WMO code table 0700
55	98	v _S	Ship's average speed made good during the three hours preceding the time of observation	WMO code table 4451
56	99-100	d _{w2} d _{w2}	Direction of secondary swell waves	Tens of degrees, WMO code table 0877; encoded 00 or 99 where applicable. Blanks = No observation of waves attempted
57	101-102	P _{w2} P _{w2}	Period of secondary swell waves	Whole seconds; encoded 99 where applicable (see under element 32)
58	103-104	H _{w2} H _{w2}	Height of secondary swell waves	Half-meter values (see under element 33)
59	105	c _i	Concentration or arrangement of sea ice	WMO code table 0639
60	106	S _i	Stage of development	WMO code table 3739
61	107	b _i	Ice of land origin	WMO code table 0439
62	108	D _i	True bearing of principal ice edge	WMO code table 0739
63	109	z _i	Present ice situation and trend of conditions over preceding three hours	WMO code table 5239
64	110		FM 13 code version	0 = previous to FM 24-V 1 = FM 24-V 2 = FM 24-VI Ext. 3 = FM 13-VII 4 = FM 13-VIII 5 = FM 13-VIII Ext. 6 = FM 13-IX 7 = FM 13-IX Ext. 8 = FM 13-X, etc.
65	111		IMMT version	0 = previous IMMT 1 = IMMT-1 (this version) 2 = IMMT-2 (next version) 3 = IMMT-3, etc.
66	112	Q ₁	Quality control indicator for (h)	0 - no quality control (QC) has been performed in this element 1 - QC has been performed; element appears to be correct 2 - QC has been performed; element appears to be inconsistent with other elements 3 - QC has been performed; element appears to be doubtful 4 - QC has been performed; element appears to be erroneous 5 - The value has been changed as a result of QC 6 - 8 Reserve 9 - The value of the element missing
67	113	Q ₂	QC indicator for (VV)	- IDEM -
68	114	Q ₃	QC indicator for (clouds: elements 12, 24-27)	- idem -
69	115	Q ₄	QC indicator for (dd)	- idem -
70	116	Q ₅	QC indicator for (ff)	- idem -

<i>Element Number</i>	<i>Character Number</i>	<i>Code</i>	<i>Element</i>	<i>Coding procedure</i>
71	117	Q6	QC indicator for (TTT)	- idem -
72	118	Q7	QC indicator for (T _d T _d T _d)	- idem -
73	119	Q8	QC indicator for (PPPP)	- idem -
74	120	Q9	QC indicator for (weather: elements 21–23)	- idem -
75	121	Q10	QC indicator for (T _w T _w T _w)	- idem -
76	122	Q11	QC indicator for (P _w P _w)	- idem -
77	123	Q12	QC indicator for (H _w H _w)	- idem -
78	124	Q13	QC indicator for (swell: elements 34–36, 56–58)	- idem -
79	125	Q14	QC indicator for (i _R RRRt _R)	- idem -
80	126	Q15	QC indicator for (a)	- idem -
81	127	Q16	QC indicator for (ppp)	- idem -
82	128	Q17	QC indicator for (D _s)	- idem -
83	129	Q18	QC indicator for (v _s)	- idem -
84	130	Q19	QC indicator for (T _b T _b T _b)	- idem -
85	131	Q20	QC indicator for ships' position	- idem -

Additional requirements for the VOSCLIM Project

86	132-134	SHD	Ship's heading in degrees true at time of observation	(000-360); e.g. 360 = North 000 = No Movement 090 = East
87	135-136	ISS	Instantaneous ship's speed in knots at time of observation	Round to nearest whole knot (00-99)
88	137-138	SLL	Maximum height in meters of deck cargo above Summer maximum load line.	(00-99); report to nearest whole meter
89	139-141	hh	Departure of reference level (Summer maximum load line) from actual sea level. Consider the difference positive when the Summer maximum load line is above the level of the sea and negative if below the water line.	position 139; blank = positive (dash) - = negative positions 140-141; (00-99) is the difference to the nearest whole meter between the Summer maximum load line and the sea level.
91	142-144	RWD	Relative wind direction in degrees off the bow	Relative wind direction; e.g. 000 = no apparent relative wind speed (calm conditions on deck). Reported direction for relative wind = 001-360 degrees in a clockwise direction off the bow of the ship. When directly on the bow, RWD = 360.

90	145-147	f 'f ' i _w	Relative wind speed reported in units indicated by (knots or m/s)	Reported in either whole knots or whole meters per second (e.g. 010 knots or 005 m/s). Units established by i _w as indicated in Character Number 27.
----	---------	--------------------------	--	---

Note: Since the relative wind speed can be greater than the true wind speed, e.g. i_w indicates knots and ff = 98, the relative wind speed may be 101 knots, therefore three positions must be allocated since i_w cannot be adjusted and the relative wind speed converted to meters per second as is done in element 15.

Note: Most of the codes (groups of letters) in the IMMT format with the exception of those added for the VOSCLIM project are defined in the Manual on Codes (WMO-No. 306) as they basically mirror the code groups used in FM 13-X Ship code. Because CBS was not persuaded to expand the FM 13-X Ship code for the VOSCLIM project the additional observed elements (selected codes) will not appear in WMO Manual on Codes (Pub. 306). Therefore an effort was made to select unique codes (groups of letters) not defined in WMO Pub. 306 for the elements added to the IMMT-2 format version modified for the VOSCLIM project. This was deliberately done to try and prevent a difference in meaning for a given code group (identical symbolic letters) in Pub 306 versus that in IMMT. Presumably none of the Character Code formats will be altered in the future by CBS